




Acoustic panels cleaning instructions

DAILY CARE

- Regularly remove dust using a soft cloth or a vacuum cleaner.
- When vacuuming, use low suction power and a soft brush attachment.
- React to any stains immediately — the sooner the stain is treated, the greater the chance it can be removed completely.



CLEANING STAINS

- In many cases, fresh stains can be removed with clean water alone, which does not damage the material.
- Gently remove excess liquid or dirt with a soft cloth or paper towel, without rubbing.
- Place a damp cotton cloth over the stain — if the cloth absorbs the stain, replace it with a clean one.
- Optionally, sparkling water may be used, as it can help lift dirt from the fibers.
- If stains remain visible, prepare a mild solution of soap and warm water.
- Apply the solution to the stained area and gently blot with a cloth or sponge, avoiding rubbing, which may damage the felt structure.
- After removing the stain, eliminate any detergent residue with clean water, dry the surface with a soft cloth, and allow the panel to air-dry naturally. Avoid speeding up the drying process with devices that emit hot air, as this may damage the material.



CLEANING WITH SPECIALIST PRODUCTS

- It is recommended to avoid untested detergents, as they may damage the felt surface.
- If water is not sufficient, more stubborn stains can be treated with proven specialist cleaning products.
- Before applying any product to a visible surface, test it in a discreet area.
- Our company offers cleaning products designed specifically for acoustic panels. Additional information is available from our representative.



WHAT TO AVOID

- Do not rub the surface — rubbing causes pilling and damages the fibers.
- Do not use aggressive chemical agents.
- Do not use excessive amounts of water — felt absorbs it easily.
- Do not dry panels directly next to heat sources, such as a hairdryer or radiator.

